## **PRODUCT DETAILS**

## FA 135

## (FA Series - Surface Mount Aluminum)

**Description:** This part is designed for 3/4" chamfered

edge walls (walls with a 45 degree cut off the corner). Model FA135 is most commonly used on poured concrete, but it may be used on granite, marble or pre-cast concrete. This part uses two SMART PINS PLUS anchors. For 1/2" chamfer, see FA 135 short.

2.0000

Material: 6061-T6 Aluminum

Ċ

0.5000

Ć

(3.5000

Finish: Hard tumble to remove all machined and/or cut edges. Type II Clear Anodize, Hard Anodize or outdoor rated Polyurethane Coat.


Product Spacing: 18" from end of planters/walls and approximately 36" center:

Anchoring: Two offset thru holes for Smart Pins Plus. Use anchors in conjunction with two-part impact resistant epoxy. C


INTELLICEPT

FA135T

This product is not intended for use on steps, stairs, sidewalk curb, or any pedestrian trafficked surfaces.



(shown in Clear Anodized)



**Finish:** Hard tumbled to remove all machined and/or cut edges. Aluminum finish options include Type II Clear Anodize or Hard Anodize.

**Corner Radius:** For 3/4" or greater chamfer corner.

Outside Dimensions: 2" (wide) x 3-1/2" (deep) x 1-1/8" (tall)

**Anchoring:** Anchored with two offset thru holes for SMART PINS PLUS anchors. Use anchors in conjunction with two-part epoxy.

**Product Spacing:** 18" from end of planters/walls and approximately 36" centers. Do not apply at grout joints.

